

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) Device (1) for sealing the barrel side of the bearing of a roll neck (2), with a sleeve (3), which is fitted on the roll neck (2) and to which a race (5) is fixed; with a bearing bush (7) supported in a chock (6); with rotary shaft seals, which are coordinated with the chock (6) by a mounting (11) and have radial lips (13, 13') that interact with the race (5); and with a sealing assembly (16) arranged in front of the rotary shaft seals towards the barrel of the roll (4), wherein the mounting (11) and the radial lips (13, 13') are ~~designed as a single part as a sealing element (8) and,~~ together with a sealing lip (15, 15') of the sealing assembly (16), form a unit that is detachably joined with the chock (6) to provide a seal, wherein amounts of oil particles that are collected can be adjusted by a size of an opening of an oil collection pocket (21) and that the amount of oil that can be stored in the oil collection pocket (21) can be set by an oblique position and a depth of the oil collection pocket (21) ~~and that the sealing~~

~~assembly (16) has an L-shaped section (17) mounted on the end face (18) of the roll (14), that a labyrinth seal (19) is formed between the sidepieces of the L-shaped section (17) and the sealing element (8), and that the sealing lip (15, 15') rests against and seals the L-shaped section (17).~~

2. (Previously presented) Device in accordance with Claim 1, wherein the sealing element (8) and the sealing lip (15) of the sealing assembly (16) are formed as a single part.

3. (Previously presented) Device in accordance with Claim 1, wherein the sealing lip (15') of the sealing assembly (16) can be detachably connected with the sealing element (8).

4. (Previously presented) Device in accordance with Claim 1, wherein the mounting (11) and/or the radial lips (13, 13') and/or the sealing lip (15, 15') of the sealing assembly (16) consist of different materials.

5. (Currently amended) Device in accordance with Claim 1, wherein the mounting (11) ~~911~~ has an extension (12), at the end of which there is at least one radial lip (13, 13') that has a sealed connection with the race (5).

6. (Previously presented) Device in accordance with Claim 5, wherein the mounting (11) and/or the radial lips (13, 13') and/or the sealing lip (15, 15') have reinforcements.

7. (Previously presented) Device in accordance with Claim 5, wherein the mounting (11) and the extension (12) have a first connection (20), by which small amounts of oil can be conveyed from an oil collection pocket (21) in the vicinity of the bearing to the region between the two radial lips (13, 13') for the purpose of lubricating the sealing lip (13) that faces away from the bearing with minimal amounts of oil, and that at least the extension (12) has a second connection (25), by which excess oil can be carried away from the region between the radial lips (13, 13').

8. (Currently amended) Device in accordance with Claim 7, wherein when the sealing element (8) has been installed, the first connection (20) in the respective upper region of the radial lips (13, 13') is located in about a ~~the~~ 12 o'clock position and that the second connection (25) in the respective lower region of the radial lips (13, 13') is located just before or just after a ~~the~~ 6 o'clock position.

9. (Canceled)

10. (Previously presented) Device in accordance with Claim 1, wherein the sealing element (8) can be adjusted on the chock (6) for the purpose of offset compensation.

11. (Previously presented) Device in accordance with Claim 10, wherein the sealing element (8) is arranged eccentrically in the chock (6).

12. (Previously presented) Device in accordance with Claim 1, wherein ~~instead of the sleeve and the bearing bush~~ are part of a friction brake, ~~an antifriction bearing system is used.~~

13. (New) Device in accordance with claim 1, wherein the bearing is an antifriction bearing.

14. (New) Device in accordance with claim 1, wherein the sealing assembly (16) has an L-shaped section (17) mounted on the end face (18) of the roll (14), a labyrinth seal (19) is formed between the sidepieces of the L-shaped section (17) and the

HM-734

sealing element (8), and the sealing lip (15, 15') rests against
and seals the L-shaped section (17).